

Product Description

La FormStrip OB is specially formulated blend of mineral oils and chemicals having release properties which are superior to those of a conventional mould oil. The chemicals react with the alkali in the concrete to form a thin water repellent skin on the surface of the mould, thereby enabling easy stripping from concrete and acting as a protection to steel and wooden formwork.

La FormStrip OB is supplied as a pale straw coloured liquid ready for direct application and use.

Uses

To provide quick, clean and easy stripping of moulds, and formwork and ensure high quality fair-faced and stain-free concrete

Advantages

- Ensures easy release, good fair-faced concrete
- Can be used on all types of formwork
- Minimises surface blemishes and staining
- Minimises cleaning of shutters before re-use
- Reduces opportunity of damage to formwork, extending usable life.

Technical Properties

Specific Gravity: 0.84 ± 0.03 at 27°C

Service Temperature: Suitable for use with steam cured concrete.

Formwork Surfaces: Equally effective on wood or metal moulds and shutters. Particularly effective on GRP and other resinous coatings including La FormStrip OB coated wooden surfaces.

Non-Staining: Does not stain concrete and can also be used safely with white cement.

Concrete Surface Quality: In addition to preventing adhesion of the cement paste to the mould or shutter face, La FormStrip OB allows air, which would otherwise be trapped, to escape from the face when the concrete is being poured and vibrated.

Pockets of air, trapped on the shuttered faces of concrete, are a major cause of imperfections, necessitating remedial work. La FormStrip OB avoids time and money spent on this.

The chemical reaction between La FormStrip OB and the cement in a concrete mix produces a strongly hydrophobic surface. This repels surplus water at the interface with the mould and by protecting the concrete from its effects, preserves uniformity of surface texture and colour.

Re-use of moulds: Due to excellent release properties, little or no deposit of cement paste remains on the shutter surface. Minimum cleaning down and further coat of La FormStrip OB renders shutters ready for reuse.

Application Instructions

Preparation of new moulds

No preparation is necessary, but if extensive reuse of timber mould is envisaged, it is advisable to protect all new surfaces with La FormStrip OB. La FormStrip OB protects timber from alkali attack which can result in a very short usable life. For used moulds, all traces of cement must be removed together with any surface deposit of previous oils.

Coating

La FormStrip OB can be applied by brush, sponge or conventional mould oil-sprayer. If a mould oil-sprayer is used, care should be taken to ensure that the correct nozzle size is chosen. Stir the contents of the container thoroughly before use. Apply one coat of La FormStrip OB thinly and evenly over the entire surface.

Only the thinnest coating necessary to achieve effective coverage should be applied. Excess application is uneconomical and may lead to surface dusting.

Wipe or brush off any particles that may remain on the surface and apply one coat of La FormStrip OB as previously. If it is required to remove La FormStrip OB completely, a strong industrial detergent should be applied together with stiff brushing and then thoroughly rinsed with clean water.

Package

La FormStrip OB is supplied in 5, 20 & 200 Litre

Coverage

A coverage between 20-30m²/Litre is possible depending upon the porosity and texture of mould surface.

Shelf Life

12 Months. It must be stirred thoroughly before use.

Health & Safety

Gloves should be worn when handling La FormStrip OB. Splashes on the skin should be removed with soap and water. Contact with eyes must be avoided and accidental contamination should be washed thoroughly with plenty of water and medical treatment sought immediately. Good ventilation should be ensured and smoking during use is prohibited.

Fire

Due to the high flash point the flammability risk of La FormStrip OB is low. Ensure adequate ventilation. Using La FormStrip OB near naked flame or smoking during use should be avoided.

Important: La Greens India Pvt. Ltd., products are guaranteed against defective materials and are sold subject to its standard terms and conditions of sale. It is the Customer's responsibility to satisfy themselves by checking with the Company whether the information is still current at the time of use. The customer must be satisfied that the product is suitable for the use intended. All products comply with the properties shown on current Technical Literatures. However, **La Greens India** does not warranty or guarantee the installation of the products as it does not have any control over installation or end use of the product. All information and particularly the recommendation relating to application and end use are given in good faith.



La Greens India Pvt. Ltd.
Old No. 151/1, New No.114, 8th Main Road,
11th Cross, Malleswaram, Bangalore-560 003
☎ +91 80 4993 4734
✉ info@lagreensindia.com
🌐 www.lagreensindia.com

- Ⓐ **Manufacturing Unit :**
Plot No.154, KIABD Indl. Area, 2nd Phase,
Antharasanahalli, Tumkur - 572106, Karnataka
- Ⓑ Goligram, Guskara Road, Near R.S. Rice Mill,
Burdwan - 713 126. West Bengal.

